

# DIESEL GENERATOR SET



## DE88E0

Image shown may not reflect actual package

Output Ratings		
Generator Set Model - 3 Phase	Prime*	Standby*
400/230 V, 50 Hz	80.0 kVA 64.0 kW	88.0 kVA 70.4 kW
480V, 60 Hz	90.0 kVA 72.0 kW	100.0 kVA 80.0 kW

\* Refer to ratings definitions on page 4.  
Ratings at 0.8 power factor.

Technical Data		
Engine Make & Model:	Cat® C4.4	
Generator Model:	LC3114D	
Control Panel:	EMCP 4.1	
Base Frame Type:	Heavy Duty Fabricated Steel	
Circuit Breaker Type:	3 Pole MCCB	
Frequency:	50 Hz	60 Hz
Engine Speed: RPM	1500	1800
Fuel Tank Capacity: litres (US gal)	219 (57.9)	
Fuel Consumption, Prime: l/hr (US gal/hr)	18.0 (4.8)	21.0 (5.5)
Fuel Consumption, Standby : l/hr (US gal/hr)	19.8 (5.2)	23.3 (6.2)

# DIESEL GENERATOR SET



## Engine Technical Data

Physical Data	
<b>Manufacturer:</b>	Caterpillar
<b>Model:</b>	C4.4
<b>No. of Cylinders/Alignment:</b>	4 / In Line
<b>Cycle:</b>	4 Stroke
<b>Induction:</b>	Turbocharged
<b>Cooling Method:</b>	Water
<b>Governing Type:</b>	Mechanical
<b>Governing Class:</b>	ISO 8528 G2
<b>Compression Ratio:</b>	17.25:1
<b>Displacement: l (cu.in)</b>	4.4 (268.5)
<b>Bore/Stroke: mm (in)</b>	105.0 (4.1)/127.0 (5.0)
<b>Moment of Inertia: kg m<sup>2</sup> (lb. in<sup>2</sup>)</b>	1.14 (3896)
<b>Engine Electrical System:</b>	
-Voltage/Ground:	12/Negative
-Battery Charger Amps:	65
<b>Weight: kg (lb) - Dry:</b>	463 (1021)
- Wet:	485 (1069)

Air System	50 Hz	60 Hz
<b>Air Filter Type:</b>	Replaceable Element	
<b>Combustion Air Flow:</b>		
m <sup>3</sup> /min (cfm)	-Standby: 5.1 (180)	6.5 (230)
	-Prime: 4.8 (170)	6.2 (219)
<b>Max. Combustion Air Intake</b>		
<b>Restriction: kPa (in H<sub>2</sub>O)</b>	8.0 (32.1)	8.0 (32.1)
<b>Radiator Cooling Air Flow:</b>		
m <sup>3</sup> /min (cfm)	121.2 (4280)	140.4 (4958)
<b>External Restriction to</b>		
<b>Cooling Air Flow: Pa (in H<sub>2</sub>O)</b>	120 (0.5)	120 (0.5)

Cooling System	50 Hz	60 Hz
<b>Cooling System Capacity:</b>		
l (US gal)	13.0 (3.4)	13.0 (3.4)
<b>Water Pump Type:</b>	Centrifugal	
<b>Heat Rejected to Water &amp; Lube Oil: kW (Btu/min)</b>		
-Standby:	51.0 (2900)	57.0 (3242)
-Prime:	46.0 (2616)	53.0 (3014)
<b>Heat Radiation to Room:</b> Heat radiated from engine and alternator		
kW (Btu/min)	-Standby: 20.7 (1177)	22.1 (1257)
	-Prime: 18.9 (1075)	20.1 (1143)
<b>Radiator Fan Load: kW (hp)</b>	1.0 (1.3)	1.7 (2.3)
Cooling system designed to operate in ambient conditions up to 50°C (122°F). Contact your local Cat dealer for power ratings at specific site conditions.		

Lubrication System	
<b>Oil Filter Type:</b>	Spin-On, Full Flow
<b>Total Oil Capacity l (US gal):</b>	8.0 (2.1)
<b>Oil Pan l (US gal):</b>	7.0 (1.8)
<b>Oil Type:</b>	API CG4 / CH4 15W-40
<b>Cooling Method:</b>	Water

Performance	50 Hz	60 Hz
<b>Engine Speed: RPM</b>	1500	1800
<b>Gross Engine Power: kW (hp)</b>		
-Standby:	80.7 (108.0)	93.0 (125.0)
-Prime:	73.4 (98.0)	84.5 (113.0)
<b>BMEP: kPa (psi)</b>		
-Standby:	1468.0 (212.9)	1409.0 (204.4)
-Prime:	1335.0 (193.6)	1280.0 (185.7)
<b>Regenerative Power: kW</b>	7.0	9.0

Fuel System				
<b>Fuel Filter Type:</b>	Replaceable Element			
<b>Recommended Fuel:</b>	Class A2 Diesel or BSEN590			
<b>Fuel Consumption: l/hr (US gal/hr)</b>				
	<b>110% Load</b>	<b>100% Load</b>	<b>75% Load</b>	<b>50% Load</b>
<b>Prime</b>				
50 Hz	19.8 (5.2)	18.0 (4.8)	13.6 (3.6)	9.5 (2.5)
60 Hz	23.3 (6.2)	21.0 (5.5)	16.1 (4.3)	11.6 (3.1)
<b>Standby</b>				
50 Hz	19.8 (5.2)	14.9 (3.9)	10.3 (2.7)	
60 Hz	23.3 (6.2)	17.7 (4.7)	12.5 (3.3)	
(based on diesel fuel with a specific gravity of 0.85 and conforming to BS2869, Class A2)				

Exhaust System	50 Hz	60 Hz
<b>Silencer Type:</b>	Industrial	
<b>Silencer Model &amp; Quantity:</b>	EXSY1 (1)	
<b>Pressure Drop Across</b>		
<b>Silencer System: kPa (in Hg)</b>	1.17 (0.345)	1.97 (0.581)
<b>Silencer Noise Reduction</b>		
<b>Level: dB</b>	16	16
<b>Max. Allowable Back</b>		
<b>Pressure: kPa (in. Hg)</b>	10.0 (3.0)	15.0 (4.4)
<b>Exhaust Gas Flow:</b>		
m <sup>3</sup> /min (cfm)	-Standby: 13.3 (470)	15.9 (560)
	-Prime: 12.5 (441)	15.0 (530)
<b>Exhaust Gas Temperature: °C (°F)</b>		
-Standby:	580 (1076)	560 (1040)
-Prime:	555 (1031)	535 (995)

# DIESEL GENERATOR SET



## Generator Performance Data

Data Item	50 Hz				60 Hz				
	415/240V	400/230V 230/115V 200/115V	380/220V 220/110V	220/127V	480/277V 240/139V	380/220V 220/110V	240/120V 208/120V		440/254V 220/127V
Motor Starting Capability* kVA	196	184	168	217	215	143	168	-	185
Short Circuit Capacity** %	300	300	300	300	300	300	300	-	300
Reactances: Per Unit									
Xd	2.535	2.728	3.023	2.255	2.558	4.081	3.405	-	3.044
X'd	0.110	0.118	0.131	0.097	0.111	0.176	0.147	-	0.132
X''d	0.066	0.071	0.078	0.058	0.066	0.106	0.088	-	0.079

Reactances shown are applicable to prime ratings.

\*Based on 30% voltage dip at 0.6 power factor and SHUNT excitation system.

\*\* With optional Permanent Magnet generator

## Generator Technical Data

Physical Data	
LC Series	
Model:	LC3114D
No. of Bearings:	1
Insulation Class:	H
Winding Pitch - Code:	2/3 - 6
Wires:	12
Ingress Protection Rating:	IP23
Excitation System:	SHUNT
AVR Model:	R250

Operating Data	
Overspeed: RPM	2250
Voltage Regulation: (steady state)	+/- 0.5%
Wave Form NEMA = TIF:	50
Wave Form IEC = THF:	2.0%
Total Harmonic Content LL/LN:	2.0%
Radio Interference:	Suppression is in line with European Standard EN61000-6
Radiant Heat: kW (Btu/min)	
-50 Hz:	6.7 (381)
-60 Hz:	7.1 (404)

# DIESEL GENERATOR SET



## Technical Data



Voltage 50 Hz	Prime		Standby	
	kVA	kW	kVA	kW
415/240V	80.0	64.0	88.0	70.4
400/230V	80.0	64.0	88.0	70.4
380/220V	80.0	64.0	88.0	70.4
230/115V	80.0	64.0	88.0	70.4
220/127V	80.0	64.0	88.0	70.4
220/110V	80.0	64.0	88.0	70.4
200/115V	80.0	64.0	88.0	70.4

Voltage 60 Hz	Prime		Standby	
	kVA	kW	kVA	kW
480/277V	90.0	72.0	100.0	80.0
220/127V	90.0	72.0	100.0	80.0
380/220V	90.0	72.0	100.0	80.0
240/120V	90.0	72.0	100.0	80.0
440/254V	90.0	72.0	100.0	80.0
220/110V	90.0	72.0	100.0	80.0
208/120V	90.0	72.0	100.0	80.0
240/139V	90.0	72.0	100.0	80.0

## Weights & Dimensions

Weights: kg (lb)	
Net (+ lube oil)	1058 (2332)
Wet (+ lube oil & coolant)	1071 (2361)
Fuel, lube oil & coolant	1256 (2770)

Dimensions: mm (in)	
Length	1925 (75.8)
Width	1120 (44.1)
Height	1361 (53.6)



**Note:** General configuration not to be used for installation. See general dimension drawings for detail.

## Definitions

### Standby Rating

Output available with varying load for the duration of the interruption of the normal source power. Average power output is 70% of the standby power rating. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year.

### Prime Rating

Output available with varying load for an unlimited time. Average power output is 70% of the prime power rating. Typical peak demand is 100% of prime rated kW with 10% overload capability for emergency use for a maximum of 1 hour in 12. Overload operation cannot exceed 25 hours per year.

### Standard Reference Conditions

Note: Standard reference conditions 25°C (77°F) air inlet temp, 100m (328ft) A.S.L. 30% relative humidity. Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, Class A2.

## General Data

### Documents

A full set of operation and maintenance manuals and circuit wiring diagrams.

### Quality Standards

The equipment meets the following standards: **IEC60034-1, IEC60034-22, ISO3046, ISO8528, NEMA MG 1-32, NEMA MG 1-33, 2004/108/EC, 2006/42/EC, 2006/95/EC.**

Performance No.: P2516A, P2516B

Feature Code: C04DE23, C04DE24, C04DE25, C04DE26, C04DE42,

C04DE43, C04DE44, C04DE45

Gen. Arr. Number: 448-4943

Source: European or China Sourced

LEHE0704-00 (08/14)

www.Cat-ElectricPower.com

© 2014 Caterpillar  
All rights reserved.

Materials and specifications are subject to change without notice. The International System of Units (SI) is used in this publication. CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.